



MARKET LEADER†



#1 LIGHT TRUCK†

#1 ORIGINAL  
EQUIPMENT TIRES†

**OVER  
30% MORE**  
MILES-TO-REMOVAL  
THAN COMPETITION††

# WRANGLER FORTITUDE HT®

STRENGTH TO TACKLE THE DEMANDS OF YOUR DAY, EVERY DAY

■ **MOVE WITH CONFIDENCE**

Stand up to the stress of heavy loads with reinforced construction.

■ **TREAD QUIETLY**

Enjoy a quiet and comfortable ride with an optimized tread design.

■ **INVEST IN MORE UPTIME**

Extend tread life with a durable tread compound.

■ **REMAIN ON TRACK ALL YEAR LONG**

Gain enhanced snow traction from full-depth sipes and biting edges.

■ **STAY STEADY AND SECURE**

Protect against hydroplaning with four deep aqua grooves.

**GOODYEAR**  
MORE DRIVEN



[www.goodyearfleetnetwork.com](http://www.goodyearfleetnetwork.com)

† Source is 2018 Modern Tire Dealer Facts Issue (page 33) and Speed Ratings and Market Share.  
†† Based on average projected miles to removal in fleet treadwear testing using tire size 235/65R16C 121R on 2016 and 2018 Ford Transit 250 cargo vans loaded to 8,716 pounds versus the following specified competitors. Average projected miles to removal: Goodyear® Wrangler Fortitude HT®: 37,925; Firestone® Transforce™ CV: 25,948; Continental® VancoFourSeason™: 28,459. Actual results may vary.



# WRANGLER FORTITUDE HT® AVAILABLE SIZES

| SIZE  | SERVICE DESCRIPTION | LOAD RANGE | SIDEWALL | PRODUCT CODE | MATERIAL NUMBER | APPROVED RIM WIDTH (INS) | MEASURING RIM WIDTH (INS) | SECTION WIDTH (INS) | OVERALL DIAMETER (INS) | MAX LOAD (LBS) | TREAD DEPTH (IN 32 <sup>nds</sup> ) | REVS/ MILE | UTQG    | OE FITMENT   |
|---|---------------------|------------|----------|--------------|-----------------|--------------------------|---------------------------|---------------------|------------------------|----------------|-------------------------------------|------------|---------|--|
| 235/75R15                                       | 105T                | SL         | BSL      | 157142622    | 233647          | 6.0 - 7.0                | 6.5                       | 9.3                 | 28.9                   | 2,039          | 12                                  | 723        | 680 A B |  |
| 225/75R16                                       | 104T                | SL         | OWL      | 157144620    | 228826          | 6.0 - 7.5                | 6.0                       | 8.8                 | 29.3                   | 1,984          | 12                                  | 713        | 680 A B |  |
| 235/70R16                                       | 106T                | SL         | BSL      | 157043622    | 228827          | 6.0 - 8.0                | 7.0                       | 9.5                 | 29.0                   | 2,094          | 12                                  | 721        | 680 A B |  |
| 235/75R16                                       | 112T                | XL         | BSL      | 157145622    | 228828          | 6.0 - 8.0                | 6.5                       | 9.3                 | 29.8                   | 2,469          | 12                                  | 701        | 680 A B |  |
| 245/70R16                                       | 107T                | SL         | OWL      | 157762620    | 228829          | 6.5 - 8.0                | 7.0                       | 9.8                 | 29.5                   | 2,149          | 12                                  | 708        | 680 A B |  |
| 245/75R16                                       | 111T                | SL         | OWL      | 157059620    | 228830          | 6.5 - 8.0                | 7.0                       | 9.8                 | 30.5                   | 2,403          | 12                                  | 685        | 680 A B |  |
| 265/70R16                                       | 112T                | SL         | BSL      | 157045622    | 222656          | 7.0 - 9.0                | 8.0                       | 10.7                | 30.6                   | 2,469          | 11                                  | 682        | 680 A B | Chevrolet Colorado: 15-17, GMC Canyon: 15-17                 |
| 265/75R16                                       | 116T                | SL         | OWL      | 157057620    | 228832          | 7.0 - 9.0                | 7.5                       | 10.5                | 31.7                   | 2,756          | 12                                  | 659        | 680 A B |  |
| 235/65R17                                       | 104T                | SL         | BSL      | 157996622    | 228833          | 6.5 - 8.5                | 7.0                       | 9.5                 | 29.0                   | 1,984          | 12                                  | 721        | 680 A B |  |
| 235/70R17                                       | 109T                | XL         | BSL      | 157078622    | 228834          | 6.0 - 8.0                | 7.0                       | 9.5                 | 30.0                   | 2,271          | 12                                  | 697        | 680 A B |  |
| 235/75R17                                       | 109T                | SL         | BSL      | 157089622    | 228835          | 6.0 - 8.0                | 6.5                       | 9.3                 | 30.9                   | 2,271          | 12                                  | 676        | 680 A B |  |
| 245/65R17                                       | 107T                | SL         | BSL      | 157592622    | 228836          | 7.0 - 8.5                | 7.0                       | 9.8                 | 29.5                   | 2,149          | 12                                  | 708        | 680 A B |  |
| 245/70R17                                       | 110T                | SL         | OWL      | 157172620    | 228837          | 6.5 - 8.0                | 7.0                       | 9.8                 | 30.6                   | 2,337          | 12                                  | 683        | 680 A B |  |
| 245/70R17                                       | 110T                | SL         | OWL      | 157060620    | 226575          | 6.5 - 8.0                | 7.0                       | 9.8                 | 30.6                   | 2,337          | 12                                  | 683        | 680 A B |  |
| 255/65R17                                       | 110T                | SL         | BSL      | 157069622    | 222654          | 7.0 - 9.0                | 7.5                       | 10.2                | 30.1                   | 2,335          | 11                                  | 691        | 680 A B | Chevrolet Colorado: 15-17, GMC Canyon: 15-17                 |
| 255/70R17                                       | 112T                | SL         | OWL      | 157067620    | 228838          | 6.5 - 8.5                | 7.5                       | 10.3                | 31.1                   | 2,469          | 12                                  | 672        | 680 A B |  |
| 265/65R17                                       | 112T                | SL         | OWL      | 157061620    | 228839          | 7.5 - 9.5                | 8.0                       | 10.7                | 30.6                   | 2,469          | 12                                  | 683        | 680 A B |  |
| 265/70R17                                       | 115T                | SL         | BSL      | 157042622    | 231043          | 7.0 - 9.0                | 8.0                       | 10.7                | 31.7                   | 2,679          | 12                                  | 659        | 680 A B |  |
| 265/70R17                                       | 115T                | SL         | OWL      | 157042620    | 222031          | 7.0 - 9.0                | 8.0                       | 10.7                | 31.7                   | 2,679          | 12                                  | 659        | 680 A B | Ford F-150: 14-17  |
| 245/60R18                                       | 105T                | SL         | BSL      | 157001622    | 228840          | 7.0 - 8.5                | 7.0                       | 9.8                 | 29.6                   | 2,039          | 12                                  | 706        | 680 A B |  |
| 255/65R18                                       | 111T                | SL         | BSL      | 157088622    | 228841          | 7.0 - 9.0                | 7.5                       | 10.2                | 31.1                   | 2,403          | 12                                  | 672        | 680 A B |  |
| 255/70R18                                       | 113T                | SL         | OWL      | 157174620    | 228842          | 6.5 - 8.5                | 7.5                       | 10.2                | 32.1                   | 2,535          | 12                                  | 651        | 680 A B |  |
| 265/60R18                                       | 110T                | SL         | BSL      | 157076622    | 222652          | 7.5 - 9.5                | 8.0                       | 10.7                | 30.5                   | 2,337          | 11                                  | 685        | 680 A B | Chevrolet Colorado: 15-17, GMC Canyon: 15-17                 |
| 265/65R18                                       | 112T                | SL         | BSL      | 157051622    | 230901          | 7.5 - 9.5                | 8.0                       | 10.7                | 31.5                   | 2,469          | 11                                  | 663        | 680 A B | Chevrolet Silverado: 17, Chevrolet Tahoe: 17, GMC Sierra: 17 |
| 265/65R18                                       | 112T                | SL         | OWL      | 157051620    | 230903          | 7.5 - 9.5                | 8.0                       | 10.7                | 31.5                   | 2,469          | 11                                  | 663        | 680 A B | Chevrolet Silverado: 17, Chevrolet Tahoe: 17, GMC Sierra: 17 |
| 265/70R18                                       | 116T                | SL         | OWL      | 157070620    | 228844          | 7.0 - 9.0                | 8.0                       | 10.7                | 32.6                   | 2,756          | 12                                  | 641        | 680 A B |  |
| 275/65R18                                       | 116T                | SL         | OWL      | 157066620    | 222027          | 7.5 - 9.5                | 8.0                       | 11.0                | 32.1                   | 2,756          | 12                                  | 651        | 680 A B | Ford F-150: 14-17, Expedition: 16-17                         |
| 275/65R18                                       | 116T                | SL         | OWL      | 157081620    | 232368          | 7.5 - 9.5                | 8.0                       | 11.0                | 32.1                   | 2,756          | 12                                  | 651        | 680 A B | Ford F-150: 18   |
| 275/65R18                                       | 116T                | SL         | VSB      | 157066708    | 228707          | 7.5 - 9.5                | 8.0                       | 11.0                | 32.1                   | 2,756          | 11                                  | 651        | 680 A B |  |
| 285/45R22                                       | 114H                | XL         | BSL      | 157176622    | 228847          | 9.0 - 10.5               | 9.5                       | 11.2                | 32.1                   | 2,601          | 12                                  | 651        | 680 A B |  |
| WRANGLER FORTITUDE HT LT                        |                     |            |          |              |                 |                          |                           |                     |                        |                |                                     |            |         |  |
| LT215/85R16                                     | 115R                | E          | BSL      | 179233622    | 236505          | 5.5 - 7.0                | 6                         | 8.6                 | 30.5                   | 2,680          | 13                                  | 688        |         |  |
| LT225/75R16                                     | 115R                | E          | BSL      | 179748622    | 228723          | 6.0 - 7.0                | 6                         | 8.8                 | 29.3                   | 2,680          | 15                                  | 710        |         |  |
| LT245/75R16                                     | 120R                | E          | BSL      | 179747622    | 228725          | 6.5 - 8.0                | 7                         | 9.8                 | 30.5                   | 3,042          | 15                                  | 682        |         |  |
| LT265/75R16                                     | 123R                | E          | OWL      | 179746620    | 228726          | 7.0 - 8.0                | 7.5                       | 10.5                | 31.7                   | 3,415          | 15                                  | 656        |         |  |
| LT235/80R17                                     | 120R                | E          | BSL      | 179235622    | 236506          | 6.0 - 7.5                | 6.5                       | 9.3                 | 31.8                   | 3,085          | 13                                  | 654        |         |  |
| LT245/75R17                                     | 121R                | E          | BSL      | 179236622    | 236507          | 6.5 - 7.5                | 7                         | 9.8                 | 31.7                   | 3,195          | 13                                  | 663        |         |  |
| LT245/70R17                                     | 119R                | E          | BSL      | 179469622    | 228728          | 6.5 - 8.0                | 7                         | 9.8                 | 30.6                   | 3,000          | 15                                  | 680        |         |  |
| LT265/70R17                                     | 121R                | E          | OWL      | 179535620    | 228730          | 7.0 - 8.5                | 8                         | 10.7                | 31.7                   | 3,195          | 15                                  | 656        |         |  |
| LT285/70R17                                     | 121R                | E          | BSL      | 179237622    | 236508          | 7.5 - 9.0                | 8.5                       | 11.5                | 32.8                   | 3,195          | 13                                  | 638        |         |  |
| LT265/70R18                                     | 124R                | E          | BSL      | 179214622    | 236509          | 7.0 - 8.5                | 8                         | 10.7                | 31.7                   | 3,525          | 13                                  | 638        |         |  |
| LT275/70R18                                     | 125R                | E          | BSL      | 179139622    | 236510          | 7.0 - 8.5                | 8                         | 11                  | 33.4                   | 3,640          | 13                                  | 630        |         |  |
| LT275/65R18                                     | 123R                | E          | BSL      | 179092622    | 236521          | 7.5 - 9.0                | 8                         | 11                  | 32.1                   | 3,415          | 13                                  | 651        |         |  |
| LT275/65R20                                     | 126R                | E          | BSL      | 179231622    | 236522          | 7.5 - 9.5                | 8                         | 11                  | 34.1                   | 3,750          | 13                                  | 610        |         |  |
| LT265/60R20                                     | 121R                | E          | BSL      | 179097622    | 236523          | 7.5 - 9.5                | 8                         | 10.7                | 32.5                   | 3,195          | 13                                  | 640        |         |  |
| LT285/60R20                                     | 125R                | E          | BSL      | 179015622    | 236524          | 8.0 - 10.0               | 8.5                       | 11.5                | 33.5                   | 3,640          | 13                                  | 622        |         |  |
| WRANGLER FORTITUDE HT COMMERCIAL SERVICE RADIAL |                     |            |          |              |                 |                          |                           |                     |                        |                |                                     |            |         |  |
| 195/75R16C                                      | 107R                | D          | BSL      | 179196622    | 234166          | 5.0 - 6.0                | 5.5                       | 7.7                 | 27.5                   | 2,150          | 11                                  | 733        |         |  |
| 225/75R16C                                      | 121R                | E          | BSL      | 179194622    | 234164          | 6.0 - 7.0                | 6                         | 8.8                 | 29.3                   | 3,195          | 11                                  | 714        |         |  |
| 235/65R16C                                      | 121R                | E          | BSL      | 179195622    | 234165          | 6.5 - 8.5                | 7                         | 9.5                 | 28                     | 3,195          | 11                                  | 746        |         |  |

## POPULAR FITMENTS

- Chevrolet 1500, 2500, 3500, Colorado, Express, Silverado, Suburban, Tahoe
- Dodge Durango
- Ford F-150, F-250, F-350, Expedition, Transit
- GMC Canyon, Sierra, Yukon
- Infiniti FX
- Jeep Grand Cherokee
- Lexus GX
- Mercedes Sprinter
- Nissan NV3500, Frontier, Pathfinder, Xterra
- Ram ProMaster
- Toyota 4Runner, Sequoia, Tundra

**PLUS-SIZING DISCLAIMER WARNING:** Before you replace tires, always consult the vehicle owner's manual and follow the vehicle manufacturer's replacement tire recommendations. Vehicle handling may be significantly affected by a change in tire size or type. When selecting tires that are different from the Original Equipment size, see a professional installer in order to make certain that proper clearance, load-carrying capacity and inflation pressure are selected. Never exceed the maximum load capacity and inflation pressure listed on the sidewall of the tire. Always drive safely and obey all traffic laws. Avoid sudden, sharp turns or lane changes. Failure to follow this warning may result in loss of control of the vehicle, leading to an accident and serious injury or death.

For more complete information, go to Tire-HQ™ at [www.tire-hq.com](http://www.tire-hq.com).  
©2019 The Goodyear Tire & Rubber Company. All rights reserved.

**GOODYEAR**  
MORE DRIVEN.